



328300



328160



328220



328260



328300




328330




328350



328370



328390



328650



328850

328000 / T328000

COM 1000

– quality and functionality for all times

COM 1000, with its stringently simple design, embodies a timeless carpet where high quality plays the leading role alongside functionality beyond the ordinary. The classic expression carries reminders of cobblestone paving, which has had significant architectural importance over time with its patterned surfaces in urban spaces. Available both as broadloom, square carpet tiles, ZigZag-Tiles[®], and as LockTiles[®].













Available in 10 timeless colours. Felt backing from +200 m².

COM 1000

328000 / T328000




Technical data

| | Standard |  Broadloom w/Textile |  Broadloom w/Felt |  Tiles |
|--|------------|--|---|---|
| Type of manufacture | ISO 2424 | Woven | Woven | Woven |
| Structure | ISO 2424 | Loop pile | Loop pile | Loop pile |
| Pile material | ISO 2424 | 100% PA6 | 100% PA6 | 100% PA6 |
| Dye method | | Solution dyed | Solution dyed | Solution dyed |
| Primary backing | ISO 2424 | PET | PET | PET |
| Secondary backing | ISO 2424 | rPET Textile | rPET Felt | TEXtiles® |
|  Dimensions/Width | ISO 3018 | Approx. 400 cm | Approx. 400 cm | 50 x 50 cm (5 m²/box) |
| Surface pile thickness | ISO 1766 | Approx. 2.00 mm | Approx. 2.00 mm | Approx. 2.00 mm |
|  Total thickness | ISO 1765 | Approx. 3.00 mm | Approx. 4.00 mm | Approx. 4.5 mm |
| Total pile mass | ISO 2424 | Approx. 400 g/m² | Approx. 400 g/m² | Approx. 400 g/m² |
|  Total mass | ISO 8543 | Approx. 1,750 g/m² | Approx. 2,100 g/m² | Approx. 3,100 g/m² |
| Stitch rate | ISO 1763 | Approx. 164,000 /m² | Approx. 164,000 /m² | Approx. 164,000 /m² |
|  Antistatic | ISO 6356 | ≤ 2 kV | ≤ 2 kV | ≤ 2 kV |
|  Classification for use | EN 1307 | 23 Domestic - Intensive use | 23 Domestic - Intensive use | 23 Domestic - Intensive use |
|  Classification for use | EN 1307 | 33 Commercial - Heavy use | 33 Commercial - Heavy use | 33 Commercial - Heavy use |
|  Luxury rating class | EN 1307 | LC1 | LC1 | LC1 |
|  Dimensional stability | EN 986 | - | - | ≤ 0,2 % |
|  Castor chair suitability | EN 985 | Intensive use | Intensive use | Intensive use |
|  Stair suitability | EN 1963 | Intensive use | Intensive use | Intensive use |
|  Impact sound reduction | ISO 10140 | Approx. ΔL _w 14 dB | Approx. ΔL _w 18 dB | Approx. ΔL _w 20 dB |
|  Sound absorption | EN ISO 354 | Approx. 0.10 a _w | Approx. 0.15 a _w | Approx. 0.20 a _w |
|  Thermal resistance | ISO 8302 | Approx. 0.06 m² K/W | Approx. 0.09 m² K/W | Approx. 0.10 m² K/W |
|  Fireclass | EN 13501-1 | C _{fl} – s1 | C _{fl} – s1 | B _{fl} – s1 |


Recommended tile installation




LockTiles®



ZigZag-Tiles®



Square






COM 1000

328000 / T328000



Certifications

| | Standard |  Broadloom w/Textile |  Broadloom w/Felt |  Tiles |
|--|--------------------------|--|---|---|
| CE | EN 14041 | 0809-CPR-19006044-C3 | 0809-CPR-19006044-C3 | 0809-CPR-19006044-C7 |
| DOP | EN 14041 | 1118#19006044-C3 | 1118#19006044-C3 | 1118#19006044-C7 |
| IACG | EN 16516 | Compliant | Compliant | Compliant |
| M1 | | Compliant | Compliant | Compliant |
| GUI | | Compliant | Compliant | Compliant |
| GUT | | Compliant | Compliant | Compliant |
| EPD - GWP A1-A3 | ISO 14025 EN 15804+A2 | 8.13 kg CO ₂ - Eq | 8.13 kg CO ₂ - Eq | 8.85 kg CO ₂ - Eq |
| PEF - LCA Scope 3 CO ₂ - Eq according to EU PEF Standard | | 8.7 kg CO ₂ - Eq | 9.2 kg CO ₂ - Eq | 10.7-11.0 kg CO ₂ - Eq |
| Reach | | Compliant | Compliant | Compliant |
| BREEAM NOR | | Compliant | Compliant | Compliant |
| Recycled content | | 100% recycled backing | 100% recycled backing | 100% recycled backing |



As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice.
For the latest technical specifications, installation and maintenance guide visit:

www.fletcocarpets.com