



367100




367100



367120



367140




367240



367270



367310



367320



367330



367350



367740



367770



367820



367850

367000

## Couture

– classic softness from the world of fashion

The silky-soft and exclusive velour quality is a true classic with exceptional acoustic properties due to its short, upright pile. Couture has found its name in the world of fashion, where velour is cherished from Paris to Copenhagen for its inherent tactility, weight, and extravagance, which adds a wondrous radiance to any garment and design.

Available in 13 luxurious colours from our warehouse. Custom colours available from +200 m<sup>2</sup>.















The EcoTEX™ and EcoTiles™ backings are made from recycled plastic bottles

# Couture



## 367000 / T367000



### Technical data


	Standard	 Broadloom w/Textile	<input type="checkbox"/> Tiles
Type of manufacture	ISO 2424	Tufted 1/10"	Tufted 1/10"
Structure	ISO 2424	Heat-set Velour	Heat-set Velour
Pile material	ISO 2424	100% PA66	100% PA66
Dye method		Continuous dyed	Continuous dyed
Primary backing	ISO 2424	PET	PET
Secondary backing	ISO 2424	EcoTEX™	EcoTiles™
 Dimensions/Width	ISO 3018	Approx. 400 cm	50 x 50 cm (5 m <sup>2</sup> /box)
Surface pile thickness		Approx. 9.00 mm	Approx. 9.00 mm
 Total thickness		Approx. 13.00 mm	Approx. 13.0 mm
Total pile mass	ISO 2424	Approx. 1,150 g/m <sup>2</sup>	Approx. 1,150 g/m <sup>2</sup>
 Total mass	ISO 8543	Approx. 2,750 g/m <sup>2</sup>	Approx. 2,750 g/m <sup>2</sup>
Stitch rate	ISO 1763	Approx. 161,540/m <sup>2</sup>	Approx. 161,540/m <sup>2</sup>
 Antistatic	ISO 6356	≤ 2 kV	≤ 2 kV
 Classification for use	EN 1307	23 Domestic - Intensive use	23 Domestic - Intensive use
 Classification for use	EN 1307	31 Commercial - Moderate	31 Commercial - Moderate
 Luxury rating class	EN 1307	LC1	LC1
 Dimensional stability	EN 986	-	≤ 0.2 %
 Castor chair suitability	EN 985	Intensive use	Intensive use
 Stair suitability	EN 1963	Occasional use	Occasional use
 Impact sound reduction	ISO 10140	Approx. ΔL <sub>w</sub> 27 dB	Approx. ΔL <sub>w</sub> 27 dB
 Thermal resistance	ISO 8302	Approx. 0.12 m <sup>2</sup> K/W	Approx. 0.12 m <sup>2</sup> K/W
 Fireclass	EN 9239-1 EN 13501-1	C <sub>fl</sub> - s1	B <sub>fl</sub> - s1

## Certifications


	Standard	 Broadloom w/Textile	 Tiles
BREEAM NOR		Compliant	Compliant
REACH Regulation	EC 1907/2006	Compliant	Compliant
POPS Regulation	EC 2019/1021	Compliant	Compliant
Recycled content		100% recycled backing	100% recycled backing




### Recommended tile installation




SW 914  
50x50 cm (diagonal)




SW 909  
50x50 cm



SW 904  
50x50 cm



25x100 cm  
50x100 cm



50x50 cm  
100x100 cm

As we continuously improve our products and testing procedures, any above declaration is subject to amendments without prior notice.  
For the latest technical specifications, installation and maintenance guide visit:

[www.fletcocarpets.com](http://www.fletcocarpets.com)